

Cordless Cross-Cutting System KSS 50 18 M bl in carrying case

ref.no.: 91B601

EAN: 4032689217413

► In metall carrying case 785x320x285mm



Technical data

Cutting depth at 0° with guide track	0 - 2 1/16 Inch
Cutting depth 45° with track	0 - 1 5/8 Inch
Cutting depth at 0° without guide track	0 - 2 5/16 Inch
Cutting depth 45° without guide track	0 - 1 7/8 Inch
Tilt range	0 – 45 °
Cutting length	16 Inch
Angle cuts	-60 – +60 °
Nominal No. of strokes – no load	4450 1/min
Weight with guide rail	12.6 lbs
Battery	18 V, 99 Wh, LiHD

Delivery specification

- 1 Allen key 5 mm; Ref. No. 093034
- 1 Guide track M, max. cutting length 400 mm (15 3/4 in.); Ref. No. 208170
- 1 Dust bag; Ref. No. 206921
- 2 Battery PowerTanks 18 M 99, 18V, 99 Wh (LiHD); Ref. No. 094503
- 1 Battery-PowerStation APS 18 M; Ref. No. 094492

Examples for usage



In view of their low weight, the 18 V versions are perfect companions when working on site. The innovative, high-capacity battery technology delivers stamina and tremendous power.



This product is part of the Cordless Alliance System. CAS means: One battery, many solutions. 100% compatibility of machines, battery packs and chargers!



The highly graduated scale permits very precise angle setting.



The fixed and adjustable stops on the underside of the rail allow the system to be used for angle cuts from $+60^\circ$ to -60° .



Thanks to the generously-sized angle scale, miter cuts always ensure a perfect fit – as seen here with exterior cladding.

Applications

- ▶ Cross cuts with guide
- ▶ Rip cuts and cross-cutting
- ▶ Plunge cuts, recesses and cutting shadow gaps from 13 mm (1/2 in.)
- ▶ Compatible materials include board materials, doors, worktops, parquet and laminate flooring, solid wood

Advantages

- ▶ The saw is compatible with the MAFELL special accessories for the corresponding mainspowered models (e.g. saw blades).
- ▶ The cross-cutting system with the latest 18 V lithium-ion technology offers unprecedented flexibility and unrestricted use with full freedom from the mains power supply.
- ▶ The machine can be removed from the cross-cut track at the single press of a button, allowing its use for the full range of applications offered by the K 55 cc.

Description

With their low weight and cutting depths of up to 52 mm on the track, MAFELL's new, powerful cross-cutting systems are making a big impact when it comes to interior work, for example.

Once the cut has been executed, the saw automatically returns to the starting position. The maximum cutting length, exploiting the full cutting depth, is 407 mm.

It is no longer necessary to unscrew the riving knife – the FLIPPKEIL offers you optimum user-friendliness and safety when plunge cutting.

Accessories / Tools

- | | | | |
|---|---|---|--|
|  | Guide track M
max. cutting length 400 mm (15 3/4 in.) |  | Guide track ML
max. cutting length 770 mm (30 5/16 in.) |
|  | Guide rail F 80
0,8 m (2,6 ft) long |  | Guide rail F 110
1.1 m (3.6 ft) long |
|  | Guide rail F 160
1.6 m (5.2 ft) long |  | Roller edge guide MF-UA |
|  | Parallel guide fence K55-PA |  | Guide rail F 210
2,1 m (6,9 ft) long |
|  | Guide rail F 310
3,1 m (10,2 ft) long |  | Connecting piece F-VS
for joining two guide rails |
|  | TCT saw blade
168 x 1,2/1,8 x 20 mm, Z 16, WZ, for ripping in wood |  | Angle fence F-WA |
|  | TCT saw blade
168 x 1,2/1,8 x 20 mm, Z 24, WZ, for universal use with wood |  | Guide pocket F 160
for guide rails up to 1,6 m |
|  | TCT saw blade
168 x 1,2/1,8 x 20 mm, Z 32, WZ, for fine sawing in wood |  | Dust bag |
|  | Guide pocket set
2 x F 160 + F-VS + 2 x F-SZ 180 MM + 1 guide pocket |  | TCT saw blade
168 x 1,2/1,8 x 20 mm, Z 56, WZ, for cross-cutting wood |
|  | Guide pocket set
F 80 + F 160 + F-WA + F-VS + 2 x F-SZ 180MM + Guide pocket |  | Battery-PowerTank 18 M 99 LiHD
Li-Ion, 18V, 99 Wh (LiHD) |
|  | End cap F-EK
2 pieces |  | Battery-PowerTank 18 M 144 LiHD
Li-Ion, 18V, 144 Wh (LiHD) |
|  | Non-slip profile F-HP 6,8 M
6.8 m (22.3 ft.) long |  | Battery-PowerStation APS 18 M
18 V |
|  | Splinter guard F-SS 3,4M
3.4 m (11.2 ft.) long |  | Battery-PowerStation APS 18M+
High-speed charger 18V |
|  | Lever clamp F-SZ 180MM
2 pieces, for fixing guide rail to workpiece |  | Suction clamping system Aeroxfix F-AF 1
with 1,3 m rail, adapters for above and underneath rail, flexible hose |
|  | Flexible hose FXS-L
up to 3,2 m (10.6 ft) long | | |

contact

MAFELL AG

Beffendorfer Straße 4
D-78727 Oberndorf / Neckar
Germany

Tel.: +49 7423 / 812-114
Fax: +49 7423 812-102
Email: export@mafell.de