

## Cordless Drill Driver A 10 M MidiMAX in the T-MAX



ref.no.: 919901

EAN: 4032689193199

► Transport and storage box T-MAX



### Technical data

|  |                |
|--|----------------|
| Chuck capacity                         | 3/8 Inch       |
| Max. drilling diameter in wood / steel | 7/8 / 3/8 Inch |
| Torque soft / hard                     | 17 / 34 Nm     |
| 1st speed range                        | 0 - 360 1/min  |
| 2nd speed range                        | 0 - 1400 1/min |
| Weight (including battery)             | 1.8 lbs        |
| Nominal voltage                        | 10,8 V         |

### Delivery specification

- 1 Quick-release chuck A-SBF 10; Ref. No. 206711
- 1 Quick-release angle head A-SWV 10; Ref. No. 206773
- 1 Battery PowerTank 10 M 22; Ref. No. 094444
- 1 Battery PowerTank 10 M 43; Ref. No. 094445
- 1 Battery PowerStation APS 10 M; Ref.No. 094447
- 1 Belt clip
- 1 Bit PZ 2

## Examples for usage

---



The 20 torque settings are easy to select with the locking collar.



Maximum torque of 34 Nm makes the A 10 M a highly capable all-rounder.



The battery charge indicator is situated on the side for permanent visibility.



Thanks to the clever angle head, screws can be tightened easily, even in confined spaces.

## Applications

---

- ▶ Drilling
- ▶ Driving
- ▶ Fitting and assembly

## Advantages

---

- ▶ With a bit holder on the top of the machine, the desired bit is always to hand.
- ▶ Spindle with 1/4" chuck directly accommodates bits and push-fit accessories.
- ▶ Bright LEDs illuminate a large working area.
- ▶ Thanks to the practical belt clip, the A 10 M is always within reach. It can be attached to the left or right of the machine without any tools.

## Description

---

Small format, big performance – the compact A 10 M drill driver raises eyebrows in its performance class thanks to exceptional output and clever functions. This handy, multi-talented machine is the ideal choice for all internal finishing tasks.

Tool-free quick-release system for speed and efficiency when alternating between drilling and driving.

The battery PowerTanks feature process-controlled technology.

All the relevant factors, including the individual cell state, air cooling and cell temperature are monitored. In addition, the floating battery cells are protected against mechanical influences.

## Accessories / Tools

---



Quick-release chuck A-SBF 10  
10 mm



Quick-release angle head A-SWV 10  
up to 100 Nm



Battery PowerTank 10 M 43  
10,8 V, 43 Wh



Quick-release bit holder A-SBH



Battery-PowerTank 10 M 22  
10,8 V, 22 Wh



Battery PowerStation APS 10 M  
10,8 V

## contact

---

MAFELL AG

Beffendorfer Straße 4  
D-78727 Oberndorf / Neckar  
Germany

Tel.: +49 7423 / 812-114  
Fax: +49 7423 812-102  
Email: [export@mafell.de](mailto:export@mafell.de)