

Orbital Disk Sander EVA 150 E / 5 in T-MAX

ref.no.: 917710

EAN: 4032689186399

▶ Transport and storage box T-MAX















Technical data

Sanding disk size Ø

Nominal No. of strokes - no load

Nominal power input

Weight

5 7/8 Inch

6000-12000 1/min

0.5 hp

4.6 lbs



Examples for usage



The compensating soft interface pad enables you to produce an outstanding finish on concave and convex surfaces. The foamed material smoothes out any unevenness and ensures consistent sanding outcomes.



Abranet® abrasive mesh is setting new standards. Around 24,000 perforations in the sanding disc facilitate extremely efficient dust extraction. Among the other benefits are a prolonged disc service life.



For coarse sanding, the EVA 150 E/5 is the ideal choice. The 5 mm stroke and a speed of 12,000 rpm represent the perfect combination for this kind of work.



Applications

- Coarse and fine sanding
- Sanding between coats
- Flat surfaces
- Curved surfaces
- Compatible materials include boards, solid wood, paint, drywall adhesive, veneered surfaces

Advantages

- Absorbers isolate the main parts of the machine that are held by hand, so that vibration generated by the sander is not transmitted to the user. This protects the user against a health hazard and makes working with the machine more pleasant.
- ▶ Thanks to the ergonomic auxiliary handle, the user can accurately guide the EVA 150 E with both hands, no matter what the sanding task. The handle can be detached when it is not required.
- Adjustable edge protection effectively avoids damage to both the workpiece and the sanding pad of the EVA 150 E.
- In combination with the multi-perforated sanding pad, powerful self-extraction creates a low-dust and safe working environment. As a consequence, the abrasive disc is less prone to clogging, disc life is prolonged, and work outcomes are improved.

Description

The EVA 150 E is the random orbital sander of choice for a high removal rate, a clean working environment, and outstanding work outcomes. An excellent finish is produced on all types of wood and board, as well as paint and other coatings, drywall adhesive and similar fillers.

It offers a 20 percent higher speed than conventional random orbital sanders, which appreciably increases the removal rate. As a result, given the same quality of surface, you can perform the work up to 20 percent quicker and ultimately save costs.

The new random orbital sander from MAFELL is also ideal for continuous operation. With a vibration emission value of less than 2.5 m/s², the EVA 150 E can be operated more or less without interruption. Soft grip surfaces ensure good control of the sander in every working position and give the machine a satisfying and secure "feel".



Accessories / Tools



Abrasive mesh Abranet® HD P 60, Ø 150 mm, 20 sheets, with interface pad in every pack



Abrasive mesh Abranet® P 100, Ø 150 mm, 40 sheets with interface pad in every pack



Abrasive mesh Abranet® P 150, Ø 150 mm, 40 sheets with interface pad in every pack



Abrasive mesh Abranet® P 240, Ø 150 mm, 40 sheets with interface pad in every pack



Interface pad EVA-SA Ø 150 mm



Universal filter bags UFB-1 5 pieces



sanding pad EVA-ST-H



Abrasive mesh Abranet® P 80, Ø 150 mm, 35 sheets with interface pad in every pack



Abrasive mesh Abranet® P 120, Ø 150 mm, 40 sheets with interface pad in every pack



Abrasive mesh Abranet® P 180, Ø 150 mm, 40 sheets with interface pad in every pack



Abrasive mesh Abranet® P 320, Ø 150 mm, 40 sheets with interface pad in every pack



Soft interface pad SAL-1 hook and loop, for curved surfaces



sanding pad EVA-ST-S soft



contact

MAFELL AG

Beffendorfer Straße 4 D-78727 Oberndorf / Neckar Germany Tel.: +49 7423 / 812-114 Fax: +49 7423 812-102 Email: export@mafell.de