


# Duo-Dowel System DD40P PowerMAX in T-MAX - GB 110 V



EAN: 4032689176734

Transport and storage box T-MAX













#### Technical data

Drill spacing	1 1/4 Inch	
Chuck Ø	5/16 Inch	
Tilt range	0 - 90 °	
Drilling depth	0 - 1 9/16 Inch	
Nominal No. of strokes – no load	13.500 1/min	
Nominal power input	1.3 hp	
Weight	6.4 lbs	
Tool Ø max.	5/8 Inch	
Tool Ø min.	3/16 Inch	
Universal motor	110 V	

## Delivery specification

- 2 Anti-slip mats, wrapped; Ref. No. 095063
- 1 Bottle for glue 250 ml (without glue); Ref. No. 095059
- 1 Allen key with handle; Ref. No. 093282
- 1 Auxiliary stops (assortment); Ref. No. 203473
- 1 Dowel nozzle Ø 8 mm; Ref. No. 095060
- 1 MAFELL special dowels 8 x 30 mm, 200 pieces
- 1 MAFELL special dowels 10 x 40 mm, 100 pieces
- 1 MAFELL special dowels 12 x 60 mm, 40 pieces



2 MAFELL dowel drill bits, carbide-tipped Ø 8, 10, 12 mm



# Examples for usage




Fast and accurate: Edge-to-edge and mitre corner joints.



For use in staircase construction, in the workshop and on site.



Quick and economical: Making carcasses with the DD40 and dowel template.



Thanks to the auxiliary stops, the edge spacing can be decreased or increased quickly and accurately.



## **Applications**

- Rows of holes
- Drilling for fittings/hardware
- Ideal for carcass and staircase construction in the workshop and on site
- Compatible materials include solid wood and board materials
- ▶ All types of joints from 5 16 mm (3/16 in. 5/8 in.)

## Advantages

- A clear scale for adjusting the material thickness and a turret with six stops enable you to reset the DD40 for a variety of thicknesses in a very short time.
- ▶ Stop system for fast and precise positioning. Retractable stop pins and auxiliary stops facilitate drilling near the edge without the need for marking.
- Continuously variable settings for drilling depth, material thickness and joint angle.
- ▶ The tilting fence is located and fastened on both sides.

### Description

The Duo-Dowel Jointer DD40 is the only portable dowel machine on the market. This MAFELL product is unparalleled worldwide.

Thanks to the use of conventional wooden dowels combined with the precise Duo-Dowel Jointer DD40, MAFELL has triggered a revolution in portable joining. Furthermore, the Duo-Dowel System DD40 is faster, more precise and less expensive than any other on the market.

The work is fastened exactly by the dowels, so that clamping is much simpler and quicker, or it can be omitted altogether.

MAFELL's DD40 System is an inclusive product package, comprising the MaxiMAX or MidiMAX machine in a T-MAX case, wooden dowels, a glue bottle, 2 anti-slip mats and drill bits as standard.



# Accessories / Tools

	Dowel drill bit-HW Ø 5 mm (3/16 in.)	Dowel drill bit-HW Ø 6 mm
	Screw clamp for fixing guide rail to workpiece	Dowel drill bit-HW Ø 6,1 mm
	Dowel drill bit-HW Ø 8 mm	Dowel drill bit-HW Ø 8,1 mm
	Dowel drill bit-HW Ø 8,2 mm	Dowel drill bit-HW Ø 10 mm (3/8 in.)
	Dowel drill bit-HW Ø 10,1 mm	Dowel drill bit-HW Ø 10,2 mm
	Dowel drill bit-HW Ø 12 mm (1/2 in.)	Dowel drill bit-HW Ø 12,2 mm
	Dowel drill bit-HW Ø 14 mm	Dowel drill bit-HW Ø 15 mm
	Dowel drill bit-HW Ø 16 mm (5/8 in.)	Dowel drill bit-HW Ø 16,2 mm
	Anti-slip mats 2 pieces	Dowel drilling template extension 1600 mm (63 in.)
-17:50	Dowel drilling template 800 mm with quick acting clamping device	 Clamping device retrofit kit for dowel template 203057
	Screw clamp with stop	



### contact

MAFELL AG

Beffendorfer Straße 4 D-78727 Oberndorf / Neckar Germany Tel.: +49 7423 / 812-114 Fax: +49 7423 812-102 Email: export@mafell.de