

Grooving Machine KFU 1000 E - GB

ref.no.: 951121

EAN: 4032689049830



- ▶ Cutting blade lock
- ▶ Powerful motor
- ▶ Large chip bag



Technical data

Cutting depth	0 - 3/16 Inch
Cutting tool Ø	4 3/4 Inch
Nominal No. of strokes – no load	8000 - 15000 1/min
Nominal power input	1.2 hp
Weight	8,4 lbs
Universal motor	110 V

Delivery specification

1 Grooving-cutting blade, TCT, elliptical, 120 x 3.6 x 20 mm (4 3/4 x 1/8 x 13/16 in.), 12 teeth; Ref. No. 091794
1 Allen key 4 mm; Ref. No. 093074

Applications

- ▶ Cutting grooves
- ▶ Compatible materials include resilient floor coverings

Advantages

- ▶ With level compensation – for constant cutting depth.
- ▶ With three rollers – to prevent tipping on uneven floors.

Description

Grooving machines are used when laying resilient floor coverings. The shape and depth of the welding rod depend on the experience of the installer and the flooring manufacturer's recommendations. Such applications in particular call for special machines that can meet these individualized requirements.

The unique feature of the KFU 1000 E is the built-in cutting blade lock for fast tool changes.

The 3.8 kg (8.4 lbs) weight and the 10 m (32.8 ft) mains cable give the KFU 1000 E freedom of movement and a large operating radius. The powerful 900 watt (1.2 hp) single-phase motor allows a speed of 8000 – 1500 rpm and an accordingly clean cutting result.

With the stepless electronic controls, you can use the machine for all types of material. Simply set the right speed and off you go!

Smallest possible wall distance: only 11.5 mm (7/16 in.).

If you prefer to work upright, we offer an exclusive additional handle as an optional accessory.

Accessories / Tools



Groove-cutting blade
elliptical, TCT, 120 x 3.6 x 20 mm (4 3/4 x 1/8 x 13/16 in.), 12 teeth



Guide roller
R 1,5



Replacement knives
for hand grooving tool, semicircular



Groove-cutting blade
elliptical, TCT, 120 x 4.2 x 20 mm (4 3/4 x 3/16 x 13/16 in.), 12 teeth



Hand grooving tool
semicircular, with 5 replacement knives



Additional handle, long

contact

MAFELL AG

Beffendorfer Straße 4
D-78727 Oberndorf / Neckar
Germany

Tel.: +49 7423 / 812-114
Fax: +49 7423 812-102
Email: export@mafell.de