Multi-Cutter MF 26 cc / 400 in carrying case - US 120 V



ref.no.: 917883

EAN: 4032689184029

- Guide track M
- With expanding groove cutter MF-VN 25
- One machine – five applications
- in carrying case

Technical data

Cutting depth	0 - 1 Inch
Nominal No. of strokes – no load	3600 - 6250 1/min
Nominal power input	1.9 hp
Weight	13.9 lbs
Universal motor	120 V

Delivery specification

1 TCT saw blade 120 x 1.2/1.8 x 20 mm (4 3/4 in.)/ AT, 24 teeth; Ref. No. 092558
1 Expanding groove cutter MF-VN 25; Ref. No. 206074
1 Parallel guide fence; Ref. No. 206038
1 Guide track M, max. cutting length 400 mm (15 3/4 in.); Ref. No. 208170
1 Mains cable 4 m - USA 120 V; Ref. No. 087830

MAFELL AG · Beffendorfer Straße 4 · 78727 Oberndorf a. N. · Germany
Telefon +49 7423 / 812-0 · Fax +49 7423 / 812-218 · E-Mail mafell@mafell.de · **www.mafell.de**

Examples for usage



When cutting crosswise grooves, typically for risers or shelves, use of the guide 400 is recommended.



Stops are provided on the underside of the rail for adjusting the angle according to the scale.



Once the machining operation has been performed, a spring automatically returns the multicutter to the starting position.



Service ducts can be cut in soft fiberboard quickly and without any dust with the MF-VN 25 expanding groove cutter.

MAFELL AG · Beffendorfer Straße 4 · 78727 Oberndorf a. N. · Germany
Telefon +49 7423 / 812-0 · Fax +49 7423 / 812-218 · E-Mail mafell@mafell.de · **www.mafell.de**

Applications

- Lengthwise and crosswise grooves
- V-grooves
- For routing wallboard prior to folding, bending techniques
- Routing and folding techniques with aluminum composite panels, sawing.
- Materials usage: solid wood, MDF, drywall, aluminum composite panels

Advantages

- Turn the adjusting screw to set the cutting depth on the sliding scale with an accuracy of 1/10 mm.
- The guard opens with a single action. When it is opened, the starting lockout and sawblade lock engage automatically.
- With or without a rail – simply turn the pointer to show the exact cutting depth.
- The MF 26 cc / 400 is permanently attached to guide M, so that the multi-cutter and the rail form an integral unit.

Description

The design of the MF 26 cc is characterized by the use of extremely rugged, high-quality and precision-made parts, including the lightweight magnesium die-cast housing and impact-resistant, fiber glass-reinforced plastic components.

The MF 26 cc multi-cutter can be operated to a cutting depth of 26 mm (1 in.) on the guide rail and as a plunge-cut saw.

Whether sawing, routing or cutting grooves, genuine precision is best achieved with the aid of the guide rail system F.

Continuously variable speed up to 6250 rpm. For shaping, sawing and slotting an abundance of different materials.

MAFELL AG · Beffendorfer Straße 4 · 78727 Oberndorf a. N. · Germany
Telefon +49 7423 / 812-0 · Fax +49 7423 / 812-218 · E-Mail mafell@mafell.de · **www.mafell.de**

Accessories / Tools



Guide track M
max. cutting length 400 mm (15 3/4 in.)



Suction hose LW 35 – 4 m long, anti-static (13.1 ft)
for use when machining solid wood



Guide fence, cpl.



Guide rail F 160
1.6 m (5.2 ft) long



Guide rail F 210
2,1 m (6,9 ft) long



Guide rail F 310
3,1 m (10,2 ft) long



Chamfer knifves



Angle fence F-WA



Guide pocket F 160
for guide rails up to 1,6 m



Guide pocket set
2 x F 160 + F-VS + 2 x F-SZ 180 MM + 1 guide pocket



Guide pocket set
F 80 + F 160 + F-WA + F-VS + 2 x F-SZ 180MM + Guide pocket



End cap F-EK
2 pieces



Non-slip profile F-HP 6,8 M
6.8 m (22.3 ft.) long



TCT saw blade
120 x 1.2/1.8 x 20 mm (4 3/4 in.)/ AT, 24 teeth, for universal use in wood



Guide track ML
max. cutting length 770 mm (30 5/16 in.)



Guide rail F 80
0,8 m (2,6 ft) long



Guide rail F 110
1.1 m (3.6 ft) long



Roller edge guide MF-UA



Expanding groove cutter MF-VN 25
Cutting width 15.4 - 25 mm



Reversible TCT knife



Connecting piece F-VS
for joining two guide rails



Wallboard cutter MF-GF 45
for 45° V-grooves up to 15 mm deep (incl. 2 position indicator)



Wallboard cutter MF-GF 90/15
for 90° V-grooves up to 15 mm deep (incl. 2 position indicators)



Reversible TCT knife



Aluminum composite cutter MF-AF 90
for 90° V-grooves up to 8 mm deep (incl. 2 position indicators and 1 chip deflector)



Aluminum composite cutter MF-AF 135
for 135° V-grooves up to 8 mm deep (incl. 2 position indicators and 1 chip deflector)



Slotting head MF-SE 3
for cutting 3 slots up to 26 mm on guide rail F



Splinter guard F-SS 3,4M
3.4 m (11.2 ft.) long

MAFELL AG · Beffendorfer Straße 4 · 78727 Oberndorf a. N. · Germany
Telefon +49 7423 / 812-0 · Fax +49 7423 / 812-218 · E-Mail mafell@mafell.de · **www.mafell.de**



TCT saw blade
120 x 1.2/1.8 x 20 mm (4 3/4 in.)/ AT, 12 teeth, for ripping



TCT saw blade
120 x 1,2/1,8 x 20 mm / 40 trapezoidal teeth , for laminate



Lever clamp F-SZ 180MM
2 pieces, for fixing guide rail to workpiece



TCT saw blade
120 x 1.2/1.8 x 20 mm (4 3/4 in.)/ FT/TT 40 teeth, for fine sawing

MAFELL AG · Beffendorfer Straße 4 · 78727 Oberndorf a. N. · Germany
Telefon +49 7423 / 812-0 · Fax +49 7423 / 812-218 · E-Mail mafell@mafell.de · **www.mafell.de**

contact

MAFELL AG

Beffendorfer Straße 4
D-78727 Oberndorf / Neckar
Germany

Tel.: +49 7423 / 812-114
Fax: +49 7423 812-102
Email: export@mafell.de