

Carpenter's Skew Notch, Lap-Joint and Tenon Cutting Machine ZK 115 Ec - USA 120 V

ref.no.: 925022

EAN: 4032689143903

► boxed



Technical data

Cutting depth at 0°	0 - 2 12/16 Inch
Tilt range	0 - 60 °
Nominal No. of strokes – no load	4050 1/min
Nominal power input	4.0 hp
Weight (with standard cutter head)	46.5 lbs
Universal motor	120 V

Delivery specification

- 1 Cutter head, cpl., Ø 150 x 115 mm (5 7/8 x 4 1/2 in.); Ref. No. 203657
- 1 Parallel guide fence; Ref. No. 203683
- 1 Allen key 10 mm; Ref. No. 093164
- 1 Screw driver Torx T 15; Ref. No. 093274

Examples for usage



The ZK 115 Ec with the guide rail.



Unsurpassed precision – approved right-angled height adjustment. Distance of noches always constant irrespective of wood tolerances.



Just position the machine on the skew notch edge of reference.



New cutter head with reversible carbide tips for extreme machining rates and optimum chip removal.

Applications

- ▶ Birdsmouth cuts and lap joints
- ▶ Compatible materials include solid wood and glue-laminated timber

Advantages

- ▶ Special machine – for all notching and facing tasks.
- ▶ Fast, precise adjustment – no test cutting necessary – considerable time-saving.
- ▶ All-round protective cover – for optimum user protection.

Description

The ZK 115 Ec – a persuasive and powerful tool offering ease of use, a tool brake and electronics with: - Smooth starting - Constant speed under load - Overload protection - No-load speed reduction to protect machine - Reduced noise emissions

The entirely newly developed 150 x 115 mm (5 7/8 x 4 1/2 in.) cutter head of the ZK 115 Ec, with 13 reversible carbide tips (9 for final, 4 for rough cutting), facilitates very high cutting rates, optimum chip removal and an extended service life.

Simply score the notch and vertical cut, set the cut indicator, notch depth and angle – and mortising can begin. It couldn't be quicker or easier!

The guide rails available as optional accessories can be used with all other MAFELL carpentry machines.

Accessories / Tools



Skew notch cutter head
cpl., Ø 150 x 115 mm (5 7/8 x 4 1/2 in.)



Cutter head
cpl., Ø 190 x 81 mm (7 1/2/ 3 3/16 inch.)



Reversible knives
80 x 12 x 1.5 mm (3 1/8 x 1/2 x 1/16 in.)



Reversible knives
60 mm (2 3/8 in.)



Guide rail
length 3 m (9.8 ft) (one piece)



Adapters (pair)
for parallel guide fence



Cutter head
cpl., Ø 236 x 50 mm (9 5/16 x 1 15/16 in.)



Reversible TCT knives



Cutter head
cpl., Ø 150 x 60 mm (5 7/8 x 2 3/8 inch)



Guide rail
length 3 m (9.8 ft) (2 pieces with connecting piece)



Guide rail extension
length 1,5 m (4.9 ft)



Reversible knives
14 x 14 x 2 mm (9/16 x 9/16 x 1/16 in.)

contact

MAFELL AG

Beffendorfer Straße 4
D-78727 Oberndorf / Neckar
Germany

Tel.: +49 7423 / 812-114
Fax: +49 7423 812-102
Email: export@mafell.de