

## Multi-Cutter MF 26 cc / 400 in carrying case - GB 110 V

ref.no.: 917882

EAN: 4032689184012



- ▶ With expanding groove cutter MF-VN 25
- ▶ One machine – five applications
- ▶ in carrying case
- ▶ Guide track M



### Technical data

|                                  |                   |
|----------------------------------|-------------------|
| Cutting depth                    | 0 - 1 Inch        |
| Nominal No. of strokes – no load | 3600 - 6250 1/min |
| Nominal power input              | 1.9 hp            |
| Universal motor                  | 110 V / 50 Hz     |
| Weight                           | 13.9 lbs          |

### Delivery specification

- 1 TCT saw blade 120 x 1.2/1.8 x 20 mm (4 3/4 in.) / AT, 24 teeth; Ref. No. 092558
- 1 Expanding groove cutter MF-VN 25; Ref. No. 206074
- 1 Parallel guide fence; Ref. No. 206038
- 1 Guide track M, max. cutting length 400 mm (15 3/4 in.); Ref. No. 208170
- 1 Mains cable 4 m - GB 110 V; Ref. No. 087803

## Examples for usage



When cutting crosswise grooves, typically for risers or shelves, use of the guide 400 is recommended.



Stops are provided on the underside of the rail for adjusting the angle according to the scale.



Once the machining operation has been performed, a spring automatically returns the multicutter to the starting position.



Service ducts can be cut in soft fiberboard quickly and without any dust with the MF-VN 25 expanding groove cutter.

## Applications

---

- ▶ Lengthwise and crosswise grooves
- ▶ V-grooves
- ▶ For routing wallboard prior to folding, bending techniques
- ▶ Routing and folding techniques with aluminum composite panels, sawing.
- ▶ Materials usage: solid wood, MDF, drywall, aluminum composite panels

## Advantages

---

- ▶ Turn the adjusting screw to set the cutting depth on the sliding scale with an accuracy of 1/10 mm.
- ▶ The guard opens with a single action. When it is opened, the starting lockout and sawblade lock engage automatically.
- ▶ With or without a rail – simply turn the pointer to show the exact cutting depth.
- ▶ The MF 26 cc / 400 is permanently attached to guide M, so that the multi-cutter and the rail form an integral unit.

## Description

---

The design of the MF 26 cc is characterized by the use of extremely rugged, high-quality and precision-made parts, including the lightweight magnesium die-cast housing and impact-resistant, fiber glass-reinforced plastic components.

The MF 26 cc multi-cutter can be operated to a cutting depth of 26 mm (1 in.) on the guide rail and as a plunge-cut saw.

Whether sawing, routing or cutting grooves, genuine precision is best achieved with the aid of the guide rail system F.

Continuously variable speed up to 6250 rpm. For shaping, sawing and slotting an abundance of different materials.

## Accessories / Tools



**Guide track M**  
max. cutting length 400 mm (15 3/4 in.)



**Suction hose LW 35** – 4 m long,  
anti-static (13.1 ft)  
for use when machining solid wood



**Guide fence, cpl.**



**Guide rail F 160**  
1.6 m (5.2 ft) long



**Guide rail F 210**  
2,1 m (6,9 ft) long



**Guide rail F 310**  
3,1 m (10,2 ft) long



**Chamfer knives**



**Angle fence F-WA**



**Guide pocket F 160**  
for guide rails up to 1,6 m



**Guide pocket set**  
2 x F 160 + F-VS + 2 x F-SZ 180 MM + 1 guide  
pocket



**Guide pocket set**  
F 80 + F 160 + F-WA + F-VS + 2 x F-SZ 180MM  
+ Guide pocket



**End cap F-EK**  
2 pieces



**Non-slip profile F-HP 6,8 M**  
6.8 m (22.3 ft.) long



**TCT saw blade**  
120 x 1.2/1.8 x 20 mm (4 3/4 in.)/ AT, 24 teeth,  
for universal use in wood



**Guide track ML**  
max. cutting length 770 mm (30 5/16 in.)



**Guide rail F 80**  
0,8 m (2,6 ft) long



**Guide rail F 110**  
1.1 m (3.6 ft) long



**Roller edge guide MF-UA**



**Expanding groove cutter MF-VN 25**  
Cutting width 15.4 - 25 mm



**Reversible TCT knife**



**Connecting piece F-VS**  
for joining two guide rails



**Wallboard cutter MF-GF 45**  
for 45° V-grooves up to 15 mm deep (incl. 2  
position indicator)



**Wallboard cutter MF-GF 90/15**  
for 90° V-grooves up to 15 mm deep (incl. 2  
position indicators)



**Reversible TCT knife**



**Aluminum composite cutter MF-AF 90**  
for 90° V-grooves up to 8 mm deep (incl. 2  
position indicators and 1 chip deflector)



**Aluminum composite cutter MF-AF 135**  
for 135° V-grooves up to 8 mm deep (incl. 2  
position indicators and 1 chip deflector)



**Slotting head MF-SE 3**  
for cutting 3 slots up to 26 mm on guide rail F



**Splinter guard F-SS 3,4M**  
3.4 m (11.2 ft.) long

**TCT saw blade**

120 x 1.2/1.8 x 20 mm (4 3/4 in.)/ AT, 12 teeth,  
for ripping

**Lever clamp F-SZ 180MM**

2 pieces, for fixing guide rail to workpiece

**TCT saw blade**

120 x 1.2/1.8 x 20 mm / 40 trapezoidal teeth , for  
laminate

**TCT saw blade**

120 x 1.2/1.8 x 20 mm (4 3/4 in.)/ FT/TT 40  
teeth, for fine sawing

## contact

---

MAFELL AG

Beffendorfer Straße 4  
D-78727 Oberndorf / Neckar  
Germany

Tel.: +49 7423 / 812-114  
Fax: +49 7423 812-102  
Email: [export@mafell.de](mailto:export@mafell.de)