

Circular Saw MS 55 - GB 110 V

ref.no.: 915722

EAN: 4032689133560

► boxed



Technical data

Weight	7.3 lbs
Cutting depth	3/8 - 2 3/16 Inch
Cutting depth at 45°	3/8 - 1 3/8 Inch
Tilt range	0 - 45 °
Nominal No. of strokes – no load	4400 1/min
Nominal power input	1.5 hp
Universal motor	110 V

Delivery specification

- 1 TCT saw blade 160 x 1.2/1.8 x 20 mm (6 5/16 in.), AT, 16 teeth; Ref. No. 092539
- 1 Allen key 5 mm; Ref. No. 093034
- 1 Guide bow; Ref. 203208
- 1 Mains cable 4 m - GB 110 V; Ref. No. 087803

Examples for usage



Always "on track" with the MS 55 and the MAFELL guide rail system.



The angle can be set exactly and fixed on the scale between 0° and 45°



Instead of the double support, the MAFELL parallel guide fence can be used. This is available as an optional accessory.



The stable solid material bar serves as an additional support and as protection for the user and the machine.

Applications

- ▶ Cross and rip cuts in extreme conditions
- ▶ Bevel cuts up to 45°
- ▶ General building/roof construction works
- ▶ Compatible materials include solid wood, timber, planks and boards

Advantages

- ▶ Important machine parts such as the base plate are made of high quality diecast magnesium - for tough use on the construction site.
- ▶ One of the strongest, most robust portable circular saws in this class - due to its high torque, no operation is too difficult for the MS 55.

Description

The saw for "tough everyday use" - the MS 55 from MAFELL. Developed for cutting under the toughest of conditions. Some of the standard features:

Rugged and indestructible, yet weighs only 3.3 kg

Like all our portable circular saws, the MS 55 also uses our guide rail system.

Exact and easy to handle.

Sawing with no ifs or buts!

Accessories / Tools



Parallel guide fence
with wing screws



Mushroom-shaped handle
as additional machine guide, with fixing screw



Guide rail F 160
1,6 m (5,2 ft) long



Guide rail F 310
3,1 m (10,2 ft) long



TCT saw blade
160 x 1.2/1.8 x 20 mm (6 5/16 in.), AT, 16 teeth,
for rip cuts in wood



TCT saw blade
160 x 1.2/1.8 x 20 mm (6 5/16 in.)/ AT, 32 teeth,
for fine cuts in wood



Guide pocket set
2 x F 160 + F-VS + 2 x F-SZ 180 MM + 1 guide
pocket



End cap F-EK
2 pieces



Splinter guard F-SS 3,4M
3,4 m (11,2 ft.) long



**Suction clamping system Aeroxfix
F-AF 1**
with 1,3 m rail, adapters for above and
underneath rail, flexible hose



Guide rail F 80
0,8 m (2,6 ft) long



Guide rail F 110
1,1 m (3,6 ft) long



Guide rail F 210
2,1 m (6,9 ft) long



Connecting piece F-VS
for joining two guide rails



Angle fence F-WA



Guide pocket F 160
for guide rails up to 1,6 m



Guide pocket set
F 80 + F 160 + F-WA + F-VS + 2 x F-SZ 180MM
+ Guide pocket



Non-slip profile F-HP 6,8 M
6,8 m (22,3 ft.) long



Lever clamp F-SZ 180MM
2 pieces, for fixing guide rail to workpiece



Flexible hose FXS-L
up to 3,2 m (10,6 ft) long

contact

MAFELL AG

Beffendorfer Straße 4
D-78727 Oberndorf / Neckar
Germany

Tel.: +49 7423 / 812-114
Fax: +49 7423 812-102
Email: export@mafell.de