

## Cross-Cutting System KSS 300 MaxiMAX in T-MAX - GB 230 V

ref.no.: 916731

EAN: 4032689916732



- ▶ with Flexi-Guide rail in delivery scope
- ▶ with 2 clamping claws for Flexi-Guide included in delivery scope
- ▶ Compact package in space-saving T-MAX



### Technical data

|                                         |                 |
|-----------------------------------------|-----------------|
| Cutting depth at 0° with guide track    | 0 - 1 9/16 Inch |
| Cutting depth 45° with track            | 0 - 1 1/16 Inch |
| Cutting depth at 0° without guide track | 0 - 1 5/8 Inch  |
| Tilt range                              | 0 - 45 °        |
| Cutting length                          | 11 13/16 Inch   |
| Angle cuts                              | -60 - +60 °     |
| Nominal No. of strokes – no load        | 8800 1/min      |
| Nominal power input                     | 1.2 hp          |
| Weight with guide rail                  | 6.6 lbs         |
| Universal motor                         | 230 V / 50 Hz   |

### Delivery specification

- 1 Flexi-Guide FX 140, 1.4 m (4.6 ft) with splinter guard; Ref. No. 204372
- 2 Clamping claws; Ref. No. 203773
- 1 TCT saw blade 120 x 1,2/1,8 x 20 mm, (4 3/4 in.) 40 flat/trapezoidal teeth; Ref. No. 092559
- 1 Guide track S, max. cutting length 292 mm (15 3/4 in.); Ref. No. 208169
- 1 Parallel guide fence; Ref. No. 203180
- 1 Hose connector; Ref. No. 203782
- 1 Allen key 4 mm; Ref. No. 093074
- 1 Mains cable 4 m - GB 230 V; Ref. No. 087802

## Examples for usage



Fastening the portable circular saw to the KSS rail creates a very practical single-handed cross-cutting system.



In combination with the roll-up Flexi-Guide FX 140, precise guided cuts up to 1.4 m (4.6 ft) long can be executed with consummate ease.



Perfect edging: the circular saw's spacers enable you easily to make exact expansion joint cuts with widths from 13 mm (1/2 in.).



One system, five saws, one case: the KSS 300 can be used as a cross-cut saw, plunge-cut saw, shadow gap saw or portable circular saw with or without the Flexi-Guide FX 140 for extra guidance when cutting.

## Applications

---

- ▶ Cross cuts with guide
- ▶ Rip cuts and cross-cutting
- ▶ Plunge cuts, recesses and cutting shadow gaps from 13 mm (1/2 in.)
- ▶ Compatible materials include board materials, doors, worktops, parquet and laminate flooring, cladding

## Advantages

---

- ▶ The pivot point of the KSS 300 is on the side, on the bottom edge of the rail. This has the advantage of requiring only a single tracing pointer for all angles – with or without the rail.
- ▶ Enables you to detach the machine from the rail in a single, quick action. The saw can then be used as a separate portable circular unit with all the functionality of the MAFELL KSP series.
- ▶ The smart stop and adjustable fence with large scale increments for exact angle settings facilitate very precise and consistent miter cuts.

## Description

---

In internal finishing, one thing is important above all else: precision. Designed for supreme handling, the KSS 300 cross-cutting system therefore focuses on all the key functions for this type of work.

Fastening the portable circular saw to the KSS rail creates a very practical single-handed cross-cutting system for bevel and miter cuts; once the cut has been executed, the saw automatically returns to the starting position.

Offering a maximum cutting depth of 42 mm, the portable circular saw delivers ample power in all situations. Thanks to magnesium die-cast components, this especially neat and lightweight saw weighs only 2.4 kg (5.3 lbs).

The entire, compact sawing system is accommodated in the T-MAX carrying case - it is an ideal tool for shadow gaps, rip, bevel, plunge and angled cuts, as well as free-hand work.

## Accessories / Tools

---



**Flexi-Guide rail FX 140**  
1,4 m (4.6 ft) with splinter guard



**Screw clamp**  
for fixing guide rail to workpiece



**Guide track S**  
max. cutting length 292 mm (11 1/2 in.)



**Dust bag**  
cpl.



**TCT saw blade**  
120 x 1.2/1.8 x 20 mm (4 3/4 in.)/ AT, 24 teeth,  
for universal use in wood



**TCT saw blade**  
120 x 1.2/1.8 x 20 mm (4 3/4 in.)/ AT, 12 teeth,  
for ripping



**TCT saw blade**  
120 x 1,2/1,8 x 20 mm / 40 trapezoidal teeth , for  
laminate



**TCT saw blade**  
120 x 1.2/1.8 x 20 mm (4 3/4 in.)/ FT/TT 40  
teeth, for fine sawing

## contact

---

MAFELL AG

Beffendorfer Straße 4  
D-78727 Oberndorf / Neckar  
Germany

Tel.: +49 7423 / 812-114  
Fax: +49 7423 812-102  
Email: [export@mafell.de](mailto:export@mafell.de)