

Cordless Portable Circular Saw K 65 18M bl in the T-MAX - GB

ref.no.: 91B721

EAN: 4032689217499

► Transport and storage box T-MAX



Technical data

Cutting depth	0 - 2 5/8 Inch
Cutting depth at 45°	0 - 2 1/16 Inch
Tilt range	0 – 45 °
Nominal No. of strokes – no load	4450 1/min
Weight	9.7 lbs
Battery	18 V, 99 Wh, Li-Ion

Delivery specification

- 1 TCT saw blade 185 x 1.2/1.8 x 20 mm, ATB, 16 teeth, Battery ideal, for ripping in wood; Ref. No. 09249
- 1 Allen key 5 mm; Ref. No. 093034
- 1 Parallel guide fence
- 1 Dust bag; Ref. No. 206921
- 2 Battery PowerTanks 18 M 99, 18V, 99 Wh (LiHD); Ref. No. 094503
- 1 Battery-PowerStation APS 18 M - GB; Ref. No. 094493

Examples for usage



This product is part of the Cordless Alliance System. CAS means: One battery, many solutions. 100% compatibility of machines, battery packs and chargers!



The chips are carried away so efficiently that the vacuum channel cannot become blocked. Users enjoy this crucial benefit when executing plunge cuts in the direction of the fibers as well.



The innovative pointer automatically follows the machine as it is tilted and therefore always accurately tracks the actual cutting edge.



Always in the picture: the battery charge can be checked at any time by pressing a button.



Dispensing with a detachable riving knife, the FLIPPKEIL permits reliable, convenient and straightforward plunge cutting.

Applications

- ▶ Cross-cutting and rip cuts
- ▶ Bevel/compound miter cuts up to 45°
- ▶ Birdsmouth cuts
- ▶ Plunge cuts
- ▶ Chamfers and grooves
- ▶ Compatible materials include solid wood, board materials, insulating materials, doors, worktops and internal finishing and renovation materials

Advantages

- ▶ Healthy working environment – due to a clean workplace and a clear view of the saw blade thanks to optimal dust extraction with the MAFELL Dust Extractors.
- ▶ The pivoting guard is retracted quickly and easily by means of a lever for convenience and safety when executing bevel and plunge cuts.
- ▶ Bright LEDs illuminate a large working area.
- ▶

Description

With the compact and ultra-performing K 65 cc, you can achieve superb quality cuts at depths of up to 67 millimeters – and this from a portable circular saw with the best power-to-weight ratio in its class. It offers all the weight and handling advantages of a 55-series machine with the cutting depth of a 65 mm model.

It is no longer necessary to unscrew the riving knife – the FLIPPKEIL offers you optimum user-friendliness and safety when plunge cutting.

Accessories / Tools



Guide track M
max. cutting length 400 mm (15 3/4 in.)



Guide rail F 80
0,8 m (2,6 ft) long



Guide rail F 160
1.6 m (5.2 ft) long



Guide rail F 210
2,1 m (6,9 ft) long



Guide rail F 310
3,1 m (10,2 ft) long



Connecting piece F-VS
for joining two guide rails



Guide pocket F 160
for guide rails up to 1,6 m



Guide pocket set
2 x F 160 + F-VS + 2 x F-SZ 180 MM + 1 guide pocket



Battery-PowerTank 18 M 99 LiHD
Li-Ion, 18V, 99 Wh (LiHD)



Battery-PowerTank 18 M 144 LiHD
Li-Ion, 18V, 144 Wh (LiHD)



Battery-PowerStation APS 18 M - GB
18 V



Battery-PowerStation APS 18M + - GB
High-speed charger 18V



Suction clamping system Aeroxfix F-AF 1
with 1,3 m rail, adapters for above and underneath rail, flexible hose



Guide track ML
max. cutting length 770 mm (30 5/16 in.)



Guide rail F 110
1.1 m (3.6 ft) long



Roller edge guide MF-UA



TCT saw blade
185 x 1.2/1.8 x 20 mm, ATB, 32 teeth, Battery
ideal, for cross-cutting wood



TCT saw blade
185 x 1.2/1.8 x 20 mm, ATB, 16 teeth, Battery
ideal, for ripping in wood



Angle fence F-WA



Dust bag



Guide pocket set
F 80 + F 160 + F-WA + F-VS + 2 x F-SZ 180MM
+ Guide pocket



End cap F-EK
2 pieces



Non-slip profile F-HP 6,8 M
6.8 m (22.3 ft.) long



Splinter guard F-SS 3,4M
3.4 m (11.2 ft.) long



Lever clamp F-SZ 180MM
2 pieces, for fixing guide rail to workpiece



Flexible hose FXS-L
up to 3,2 m (10.6 ft) long

contact

MAFELL AG

Beffendorfer Straße 4
D-78727 Oberndorf / Neckar
Germany

Tel.: +49 7423 / 812-114
Fax: +49 7423 812-102
Email: export@mafell.de