Jig Saw P1 cc MaxiMAX case in the T-MAX - GB 230 V

ref.no.: 917121

EAN: 4032689171418

- Transport and storage box T-MAX

Technical data

Nominal power input	1.2 hp
Universal motor	230 V / 50 Hz
No-load number of strokes	800-3000 1/min
Weight	5.5 lbs
Stroke height	1 Inch

Delivery specification

3 jig saw blades CUnex W1, W2, W+P2
1 Parallel guide fence P1-PA; Ref. No. 205448
1 base plate P1-GP; Ref. No. 204350
1 hose connector P1-AS; Ref. No. 203917
1 chip deflector P1-SA; Ref. No. 204353
1 splinter guard P1-SS; Ref. No. 205447
1 glider P1-G; Ref. No. 205464
1 Mains cable 4 m (13.1 ft)

MAFELL AG · Beffendorfer Straße 4 · 78727 Oberndorf a. N. · Germany
Telefon +49 7423 / 812-0 · Fax +49 7423 / 812-218 · E-Mail mafell@mafell.de · **www.mafell.de**

Examples for usage



Innovative CUmax sawblade clamping ensures a positive fit because of a wedge pushing against the blade. This design reliably fastens the sawblade so that it cannot be displaced.

In order not to compromise the strength of the standard sole plate, a separate tilting plate was developed for the P1 cc.

The CUnex W1 consists of two separate, soldered sawblades. The blade‘s strength and wedge shape ensure precise and square sawing, even when cutting curves.

If exactly straight cuts are required, the P1 cc can be used in conjunction with the MAFELL F guide rail.

MAFELL AG · Beffendorfer Straße 4 · 78727 Oberndorf a. N. · Germany
Telefon +49 7423 / 812-0 · Fax +49 7423 / 812-218 · E-Mail mafell@mafell.de · **www.mafell.de**

Applications

- Straight cuts with guide rail and CUnex
- Guided circle cutting with P1-PA parallel fence and CUnex
- Recesses
- Bevel cuts up to 45°
- Compatible materials depend on sawblade; see special accessories/tools

Advantages

- The iF Product Design Award 2011 for the Jig Saw P1 cc.
- To change the sawblade, simply release the locking lever. With just one hand, effortlessly remove the blade and insert the replacement.
- The high-performance CUprex compact motor delivers consistently high speeds, even when executing long cuts.
- The vacuum channel integrated in the sole plate guarantees outstanding dust extraction directly alongside the sawblade.

Description

Owing to its ergonomic design, with low center of pressure and soft pads, the P1 cc is comfortable to hold in every situation.

Sophisticated self-extraction and a clever integrated blower keep the work surface free from chips, even if a dust extractor is not connected. The workplace therefore remains clean at all times.

The P1 cc offers continuously variable speeds in the range 800 to 3000 strokes/min., so that the output can be adjusted exactly to suit the material.

The sole plate, with integrated vacuum channel, is as sturdy as it looks. By way of a quick-release mechanism, it remains reliably fastened to the saw at an exact right angle.

Its intelligent accessories give the P1 cc unprecedented versatility. The innovative design of the new MAFELL precision sawblade CUnex W1, in particular, facilitates extremely precise sawing.

MAFELL AG · Beffendorfer Straße 4 · 78727 Oberndorf a. N. · Germany
Telefon +49 7423 / 812-0 · Fax +49 7423 / 812-218 · E-Mail mafell@mafell.de · **www.mafell.de**

Accessories / Tools

Jig saw blade CUnex W1
2 pieces

Jig saw blade W2
5 pieces

Jig saw blade W3
5 pieces

Jig saw blade W4
5 pieces

Jig saw blade W5
5 pieces

Jig saw blade W6
5 pieces

Jig saw blade W+P2
5 pieces

Jig saw blade W+M2
5 pieces

Jig saw blade L2
5 pieces

Jig saw blade M2
5 pieces

Jig saw blade E+F2
1 piece

Assortment 1
4 x W2, W+P2, W5, W4, 2 x CUnex W1

Assortment 2
4 x M2, W6, L2, W+M2, 2 x CUnex W1

Paralle guidel fence P1-PA
incl. circular cutter

Tilting plate P1-SP
tilting range +/- 45°

Splinter guard P1-SS
5 pieces

Guide rail F 80
0,8 m (2,6 ft) long

Guide rail F 110
1.1 m (3.6 ft) long

Guide rail F 160
1.6 m (5.2 ft) long

Guide rail F 210
2,1 m (6,9 ft) long

Guide rail F 310
3,1 m (10,2 ft) long

Connecting piece F-VS
for joining two guide rails

Angle fence F-WA

Guide pocket F 160
for guide rails up to 1,6 m

Guide pocket set
2 x F 160 + F-VS + 2 x F-SZ 180 MM + 1 guide pocket

Guide pocket set
F 80 + F 160 + F-WA + F-VS + 2 x F-SZ 180MM + Guide pocket

End cap F-EK
2 pieces

Non-slip profile F-HP 6,8 M
6.8 m (22.3 ft.) long

Splinter guard F-SS 3,4M
3.4 m (11.2 ft.) long

Lever clamp F-SZ 180MM
2 pieces, for fixing guide rail to workpiece

Flexible hose FXS-L
up to 3,2 m (10.6 ft) long

MAFELL AG · Beffendorfer Straße 4 · 78727 Oberndorf a. N. · Germany
Telefon +49 7423 / 812-0 · Fax +49 7423 / 812-218 · E-Mail mafell@mafell.de · **www.mafell.de**

contact

MAFELL AG

Beffendorfer Straße 4
D-78727 Oberndorf / Neckar
Germany

Tel.: +49 7423 / 812-114
Fax: +49 7423 812-102
Email: export@mafell.de