

Groove-Cutting Machine NFU 50 - GB 230 V

ref.no.: 918721

EAN: 4032689212609

▶ boxed



Technical data

Nominal voltage	230 V
Nominal power input	3.1 hp
Cutting depth at 0° without guide track	0 - 1 15/16 Inch
Cutting depth at 0° with guide track	0 - 1 3/4 Inch
Tilt range	0 - 45 °
Nominal No. of strokes – no load	5900 1/min
Weight with guide rail	20.7 lbs
Dimensions (W x L x H) with guide L	14 9/16 x 31 7/8 x 11 Inch
Cutting length with guide L	14 9/16 Inch

Delivery specification

- 1 Cutter head Ø 163 x 60 mm (6 7/16 x 2 3/8 in.); Ref. No. 091901
- 1 position indicator NFU-PA; Ref. No. 207467
- 1 Side fence SA 625; Ref. No. 207183
- 1 parallel fence; Ref. No. 207468
- 1 Guide track L, max. cutting length 370 mm (14 9/16 in.); Ref. No. 208171
- 2 repeat fence; Ref. No. 206026
- 1 allen key SW 6; Ref. No. 207496
- 1 Screw driver Torx T 15; Ref. No. 093274
- 1 Mains cable 11 m

Examples for usage



The NFU 50's sheer strength and outstanding motive power permits cuts 60 mm (2 3/8 in.) wide and 50 mm (1 15/16 in.) deep.



Individual tenons can be executed effortlessly with the NFU 50 and guide L.



The NFU 50 can also be used as a skew notch and tenon cutter.



Grooves measuring 22 mm (7/8 in.) to 40 mm (1 9/16 in.) can be produced using the expanding groove cutter available as an optional accessory.

Applications

- ▶ Lengthwise and crosswise grooves
- ▶ Frieze blocks (with guide)
- ▶ Panels in half-timbered buildings, false floors
- ▶ Angled grooves up to 45°
- ▶ Tenons
- ▶ Compatible materials include solid wood and board materials

Advantages

- ▶ The rotating 58 mm (2 5/16 in.) hose connector for large volumes of dust can be positioned by means of a locking function.
- ▶ The 2-in-1 functionality allows the cutting depth to be set quickly and easily.
- ▶ The hydraulic brake stops the tool within 3 seconds. The flashing LED lamp indicates to the user that the cutter is still turning.
- ▶ The NFU can be removed from the cross-cut track at the single press of a button, allowing its use either freehand or on the guide rail.

Description

Groove cutting machine NFU 50 offers flexibility of use and is an all-rounder capable of executing an enormous range of timberconstruction tasks. An extensive range of accessories opens up further possibilities for day-to-day work.

The design of the NFU 50 is characterized by the use of extremely rugged, high-quality and precision-made parts, including the lightweight magnesium die-cast housing and impact-resistant, fiber glass-reinforced plastic components. It also features clever technical details to help you meet the rigors of the job.

Accessories / Tools

	Guide track L max. cutting length 370 mm (14 9/16 in.)		Guide rail length 3 m (9.8 ft) (2 pieces with connecting piece)
	Guide rail length 3 m (9.8 ft) (one piece)		Guide rail extension length 1,5 m (4.9 ft)
	Guide rail F 80 0,8 m (2,6 ft) long		Machine holder S200-MH
	Adapters (pair) for parallel guide fence		Guide rail F 110 1.1 m (3.6 ft) long
	Guide rail F 160 1.6 m (5.2 ft) long		Roller edge guide K 85-UA
	Guide rail F 210 2,1 m (6,9 ft) long		Guide rail F 310 3,1 m (10,2 ft) long
	Connecting piece F-VS for joining two guide rails		Angle fence F-WA
	Extraction hose 5 m (16 ft.) Ø 49mm (1 15/16 in.) with hose connector 58mm (2 5/16 in.), Ø 66mm (2 5/8 in.) bayonet catch, static dissipative		Guide pocket F 160 for guide rails up to 1,6 m
	Guide pocket set 2 x F 160 + F-VS + 2 x F-SZ 180 MM + 1 guide pocket		Guide pocket set F 80 + F 160 + F-WA + F-VS + 2 x F-SZ 180MM + Guide pocket
	End cap F-EK 2 pieces		Non-slip profile F-HP 6,8 M 6.8 m (22.3 ft.) long
	Expanding groove cutter Ø 163 x 22 - 40 mm		Splinter guard F-SS 3,4M 3.4 m (11.2 ft.) long
	Lever clamp F-SZ 180MM 2 pieces, for fixing guide rail to workpiece		Universal guide support
	Cutter head Ø 163 x 60 mm (6 7/16 x 2 3/8 in.)		Reversible knives 14 x 14 x 2 mm (9/16 x 9/16 x 1/16 in.)
	Side fence SA 625		

contact

MAFELL AG

Beffendorfer Straße 4
D-78727 Oberndorf / Neckar
Germany

Tel.: +49 7423 / 812-114
Fax: +49 7423 812-102
Email: export@mafell.de