


## Milling templates Arunda 160B Midi

ref.no.: 91A714

EAN: 4032689216775



### Technical data

Tenon on timber width	6 - 12 Inch
Timber height	3 1/2 - 16 Inch
Timber section	6 x 3 1/2 - 12 x 16 Inch

### Delivery specification

- 1 pair of jigs
- 1 wooden box

## Examples for usage

---



Dovetailed joints on floor joists or rafter (roof system).



Speed: 8 to 18 mortise/tenon joints per hour.



Perpendicular or angled joints on floor joists or rafter (roof system).



The Arunda system is delivered in a practical wooden box.

## Applications

---

- ▶ dovetailed wood-to-wood joints
- ▶ Perpendicular or angled joints on floor joists or rafter (roof system).
- ▶ Just as easy to use in the work-shop as on the job site.

## Advantages

---

- ▶ Push-down dovetail assembly is very fast and easy. No need to pull apart the load-bearing beams to insert tenons.
- ▶ Double-cone self-tightening joints.
- ▶ Identical router bit setting to cut both mortise and tenon.

## Description

---

Arunda is a system for manually making dovetailed wood-to-wood joints to assemble timber frame structures.

All you need is a pair of Arunda jigs (one for the tenon and the other for the mortise), a powerful Mafell router LO 65 Ec equipped with the special Arunda cutter and some accessories.

There are several models available but only one size will be selected to fit your most commonly used timber widths. Keep in mind: The bigger the joint, the greater and better its resistance!

## Accessories / Tools

---



Adapter for router bit M12x1  
(ARUNDA)



Guide ring Standard - 26  
for LO 65 Ec + 2 screws



Positioning gauge Standard - 26 Trio



ARUNDA fast lever clamp  
40 x 14 cm



Arunda dovetail bit Standard - 26  
with reversible blades



Expansion plate Ø290 mm (with  
screws)  
for jigs 60-1B, 160B



Arunda blade Standard-26 reversible  
carbide blade HM  
5 pairs, skin-wrapped



Adjustable female fence 160B

## contact

---

MAFELL AG

Beffendorfer Straße 4  
D-78727 Oberndorf / Neckar  
Germany

Tel.: +49 7423 / 812-114  
Fax: +49 7423 812-102  
Email: [export@mafell.de](mailto:export@mafell.de)